

COLUMBUS FIRE DEPARTMENT

1101 JACKSON STREET COLUMBUS, INDIANA 47201 HOME OF THE FIRST DIESEL FIRE ENGINE IN 1939

(812) 376-2679 (812)-376-2568- FAX

KRISTEN BROWN, MAYOR

L. DAVID ALLMON, CHIEF

PRE-INSPECTION FIRE CHECKLIST

Fire inspectors look at many items in your place of business. So that you may have a better idea and understanding of what to keep an eye on in regard to maintenance, we have provided the following checklist:

A. EXITS	
Door/aisle is not obstructed. Proper lock/hardware on exit door. (No flush bolts, hasps, etc.) Exit doors open easily. There is a sign over the main entrance, "This door to remain unlocked during business hours," if the door has a double-keyed deadbolt.	Illuminated exit signs maintained in working order. Means of egress shall be kept clear. Emergency lights maintained and in working order. Doors with panic hardware shall have no other locking devices. Maximum occupancy signage shall be posted in a conspicuous location near the main entrance for assembly occupancies.
B. EXTINGUISHERS/FIRE PROTECTION EQUIPM Minimum 2A10BC extinguisher(s) installed. Extinguisher has been serviced within the past year and a new service tag is attached. Extinguisher is securely mounted or in an approved cabinet. Fire extinguisher not obstructed. Fire extinguisher top does not exceed 5' from floor as mounted. Standpipe shall be tested every 5 years.	ENT Hood extinguishing system maintained, and six month service and cleaning documented. Class K extinguisher installed 10-20ft from hood and duct system. Fire alarm system in proper working order – system tested annually and records kept. 18" clearance between storage and sprinkler head. Sprinkler system shall be maintained and tested annually.
C. ELECTRICAL No extension cords in use in place of permanent wiring. There are no spliced or frayed cords/wires. Spacer(s) in electrical panel gap(s) provided. No broken or faulty switch/outlets. No exposed wire in conduit. No missing/broken electrical cover plate(s). D. APPLIANCES/MECHANICAL DEVICES No propane used/stored in building.	Electrical panel is not overloaded/obstructed. No multi-plug adapters in use, other than approved power strips. Circuit breakers are labeled. Electrical cords do not extend through walls, ceilings and floors or under doors or floor coverings. 30" clearance maintained in front of electrical panels. All appliances are properly connected and vented.
E. STORAGE/COMBUSTIBLE MATERIAL/HOUSEK Flammable liquid properly stored. Oil rags in con-combustible container with lid. "No Smoking" signs installed as required. No combustible material stored near ignition source. Maintain clear and visible access to and around fire department connection.	
F. MISCELLANEOUS ———————————————————————————————————	Rapid key entry box maintained by property owner. Charcoal grills, propane grills and/or other open-flame cooking devices shall not be located on combustible balconies or within 10° of combustible construction. EXCEPTIONS: 1) One and two family dwellings, and 2) Where balconies/decks are protected by an automatic sprinkler system.